

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180613 – EX6009  
**Report Reference** EX4294 – 20120829  
**Issue Date** 2018-JUNE-13

**Issued to:** BERMAD INC  
9424 W LITTLE YORK RD  
HOUSTON TX 77040-3316

**This is to certify that representative samples of** Fire Pump Relief Valves  
See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 1739, Pilot-Operated Pressure Control Valves for Fire-Protection Service  
UL 1478, Safety for Fire Pump Relief Valves  
ANSI/NFPA 20, "Installation of Stationary Pumps for Fire Protection."

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180613 – EX6009  
**Report Reference** EX4294 – 20120829  
**Issue Date** 2018-JUNE-13


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## Addendum -

Fire pump pressure relief valves as indicated below:

Model	Size, NPS	Rated Inlet Pressure, psi (kPa)	Pilot Valve	End Configuration
43T	1-1/2, 2	365 (2515)	3-PB-16	Threaded-NPT or BSP
43T	1-1/2, 2, 2-1/2, 3, 4, 6	365 (2515)	3-PB-16	150#/PN16 Flange, Grooved
43T	1-1/2, 2, 2-1/2, 3, 4, 6	365 (2515)	3-PB-25	300#/PN25 Flange, Grooved
43T	8	365 (2515)	3-UL-16	150#/PN16 Flange, Grooved
43T	8	365 (2515)	3-UL-30	300#/PN25 Flange, Grooved
43T	10	365 (2515)	3-UL-16	150#/PN16 Flange
43T	10	365 (2515)	3-UL-30	300#/PN25 Flange

3-PB-16/3-UL-16 pilot valves are rated for a maximum set pressure of 60-235 psig  
3-PB-25/3-UL-30 pilot valves are rated for a maximum set pressure of 125-365 psig.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

