



<b>WW</b>	<b>2"</b>	<b>C70</b>	<b>SP</b>	<b>C</b>	<b>D</b>	<b>16</b>	<b>EV</b>	<b>S</b>																																																																																																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Sector</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Waterworks</td> <td>WW</td> </tr> </tbody> </table>		Sector	Code	Waterworks	WW	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Body Material</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Ductile Iron</td> <td>C</td> </tr> <tr> <td>Nylon</td> <td>P</td> </tr> <tr> <td>Ductile Iron Body with Nylon Neck &amp; Cover (C50)</td> <td>J</td> </tr> <tr> <td>Stainless Steel (A71, A72, C50, C70, C75)</td> <td>N</td> </tr> <tr> <td>Stainless Steel Body with Nylon Neck &amp; Cover (C50)</td> <td>G</td> </tr> <tr> <td>Cast Steel / WCB (A72, C70, C75)</td> <td>S</td> </tr> </tbody> </table>		Body Material	Code	Ductile Iron	C	Nylon	P	Ductile Iron Body with Nylon Neck & Cover (C50)	J	Stainless Steel (A71, A72, C50, C70, C75)	N	Stainless Steel Body with Nylon Neck & Cover (C50)	G	Cast Steel / WCB (A72, C70, C75)	S	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Coating</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Epoxy UV Protected Blue</td> <td>EV</td> </tr> <tr> <td>Epoxy AS Standard Blue</td> <td>ET</td> </tr> </tbody> </table>		Coating	Code	Epoxy UV Protected Blue	EV	Epoxy AS Standard Blue	ET	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Outlet Types</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Side</td> <td>S</td> </tr> <tr> <td><b>Down (C50, C70, C75)</b></td> <td><b>D</b></td> </tr> <tr> <td>Mushroom (C70, C75)</td> <td>M</td> </tr> </tbody> </table>		Outlet Types	Code	Side	S	<b>Down (C50, C70, C75)</b>	<b>D</b>	Mushroom (C70, C75)	M	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Additional Attributes</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>3/4" Female threaded Outlet (3/4"-1" A10/A30, C10/C30)</td> <td>t</td> </tr> <tr> <td><b>Insect Screen (C70, C75 Side or Down Outlets)</b></td> <td><b>S</b></td> </tr> <tr> <td>Lower Service Port 1/8" NPT (3/4"-1" A30, C30) or 1/4" NPT (2"-C30, C70)</td> <td>P</td> </tr> <tr> <td>stainless Steel Float (C50)</td> <td>N</td> </tr> <tr> <td>Upper Service Port 1/2" NPT (C70, C75)</td> <td>U</td> </tr> <tr> <td>Drainage Valve (C50, C70)</td> <td>Z</td> </tr> <tr> <td>Stainless Steel lower float</td> <td>N</td> </tr> </tbody> </table>		Additional Attributes	Code	3/4" Female threaded Outlet (3/4"-1" A10/A30, C10/C30)	t	<b>Insect Screen (C70, C75 Side or Down Outlets)</b>	<b>S</b>	Lower Service Port 1/8" NPT (3/4"-1" A30, C30) or 1/4" NPT (2"-C30, C70)	P	stainless Steel Float (C50)	N	Upper Service Port 1/2" NPT (C70, C75)	U	Drainage Valve (C50, C70)	Z	Stainless Steel lower float	N	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>End Connections / Pressure Ratings</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td colspan="2" style="text-align: center;"><b>Threaded</b></td> </tr> <tr> <td>BSP Male</td> <td>BP</td> </tr> <tr> <td>BSP Male PN25 (A71)</td> <td>B5</td> </tr> <tr> <td>BSP Female PN16 (C70)</td> <td>BA</td> </tr> <tr> <td>BSP Female PN25 (C70)</td> <td>BB</td> </tr> <tr> <td>BSP Female PN40 (C70)</td> <td>B3</td> </tr> <tr> <td>NPT Female 230 psi (C70)</td> <td>NA</td> </tr> <tr> <td>NPT Female 360 psi (C70)</td> <td>NB</td> </tr> <tr> <td>NPT Female 580 psi (C70)</td> <td>N3</td> </tr> <tr> <td>NPT Male</td> <td>NP</td> </tr> <tr> <td>NPT Male 360 psi (A71)</td> <td>N5</td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>Flanged</b></td> </tr> <tr> <td>ABNT 10</td> <td>B1</td> </tr> <tr> <td>ABNT 16</td> <td>B6</td> </tr> <tr> <td>ABNT 25</td> <td>B2</td> </tr> <tr> <td>ANSI 150 230 psi</td> <td>A5</td> </tr> <tr> <td>ANSI 300 360 psi (C70, C75)</td> <td>A3</td> </tr> <tr> <td>ANSI 300 580 psi (C70, C75)</td> <td>A9</td> </tr> <tr> <td>AS 16</td> <td>SA</td> </tr> <tr> <td>AS 35</td> <td>SB</td> </tr> <tr> <td>BSTD</td> <td>BD</td> </tr> <tr> <td>ISO PN10</td> <td>10</td> </tr> <tr> <td><b>ISO PN16</b></td> <td><b>16</b></td> </tr> <tr> <td>ISO PN25</td> <td>25</td> </tr> <tr> <td>ISO PN40</td> <td>40</td> </tr> <tr> <td>Universal for ISO 10/16, AS16 connected to BSP Male</td> <td>FF</td> </tr> <tr> <td>Universal for ANSI 150 connected to NPT Male</td> <td>FN</td> </tr> </tbody> </table>		End Connections / Pressure Ratings	Code	<b>Threaded</b>		BSP Male	BP	BSP Male PN25 (A71)	B5	BSP Female PN16 (C70)	BA	BSP Female PN25 (C70)	BB	BSP Female PN40 (C70)	B3	NPT Female 230 psi (C70)	NA	NPT Female 360 psi (C70)	NB	NPT Female 580 psi (C70)	N3	NPT Male	NP	NPT Male 360 psi (A71)	N5	<b>Flanged</b>		ABNT 10	B1	ABNT 16	B6	ABNT 25	B2	ANSI 150 230 psi	A5	ANSI 300 360 psi (C70, C75)	A3	ANSI 300 580 psi (C70, C75)	A9	AS 16	SA	AS 35	SB	BSTD	BD	ISO PN10	10	<b>ISO PN16</b>	<b>16</b>	ISO PN25	25	ISO PN40	40	Universal for ISO 10/16, AS16 connected to BSP Male	FF	Universal for ANSI 150 connected to NPT Male	FN
Sector	Code																																																																																																																		
Waterworks	WW																																																																																																																		
Body Material	Code																																																																																																																		
Ductile Iron	C																																																																																																																		
Nylon	P																																																																																																																		
Ductile Iron Body with Nylon Neck & Cover (C50)	J																																																																																																																		
Stainless Steel (A71, A72, C50, C70, C75)	N																																																																																																																		
Stainless Steel Body with Nylon Neck & Cover (C50)	G																																																																																																																		
Cast Steel / WCB (A72, C70, C75)	S																																																																																																																		
Coating	Code																																																																																																																		
Epoxy UV Protected Blue	EV																																																																																																																		
Epoxy AS Standard Blue	ET																																																																																																																		
Outlet Types	Code																																																																																																																		
Side	S																																																																																																																		
<b>Down (C50, C70, C75)</b>	<b>D</b>																																																																																																																		
Mushroom (C70, C75)	M																																																																																																																		
Additional Attributes	Code																																																																																																																		
3/4" Female threaded Outlet (3/4"-1" A10/A30, C10/C30)	t																																																																																																																		
<b>Insect Screen (C70, C75 Side or Down Outlets)</b>	<b>S</b>																																																																																																																		
Lower Service Port 1/8" NPT (3/4"-1" A30, C30) or 1/4" NPT (2"-C30, C70)	P																																																																																																																		
stainless Steel Float (C50)	N																																																																																																																		
Upper Service Port 1/2" NPT (C70, C75)	U																																																																																																																		
Drainage Valve (C50, C70)	Z																																																																																																																		
Stainless Steel lower float	N																																																																																																																		
End Connections / Pressure Ratings	Code																																																																																																																		
<b>Threaded</b>																																																																																																																			
BSP Male	BP																																																																																																																		
BSP Male PN25 (A71)	B5																																																																																																																		
BSP Female PN16 (C70)	BA																																																																																																																		
BSP Female PN25 (C70)	BB																																																																																																																		
BSP Female PN40 (C70)	B3																																																																																																																		
NPT Female 230 psi (C70)	NA																																																																																																																		
NPT Female 360 psi (C70)	NB																																																																																																																		
NPT Female 580 psi (C70)	N3																																																																																																																		
NPT Male	NP																																																																																																																		
NPT Male 360 psi (A71)	N5																																																																																																																		
<b>Flanged</b>																																																																																																																			
ABNT 10	B1																																																																																																																		
ABNT 16	B6																																																																																																																		
ABNT 25	B2																																																																																																																		
ANSI 150 230 psi	A5																																																																																																																		
ANSI 300 360 psi (C70, C75)	A3																																																																																																																		
ANSI 300 580 psi (C70, C75)	A9																																																																																																																		
AS 16	SA																																																																																																																		
AS 35	SB																																																																																																																		
BSTD	BD																																																																																																																		
ISO PN10	10																																																																																																																		
<b>ISO PN16</b>	<b>16</b>																																																																																																																		
ISO PN25	25																																																																																																																		
ISO PN40	40																																																																																																																		
Universal for ISO 10/16, AS16 connected to BSP Male	FF																																																																																																																		
Universal for ANSI 150 connected to NPT Male	FN																																																																																																																		
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Size</th> <th></th> </tr> </thead> <tbody> <tr> <td>3/4"</td> <td>DN20</td> </tr> <tr> <td>1"</td> <td>DN25</td> </tr> <tr> <td><b>2"</b></td> <td><b>DN50</b></td> </tr> <tr> <td>3"</td> <td>DN80</td> </tr> <tr> <td>4"</td> <td>DN100</td> </tr> <tr> <td>6"</td> <td>DN150</td> </tr> <tr> <td>8"</td> <td>DN200</td> </tr> <tr> <td>10"</td> <td>DN250</td> </tr> <tr> <td>12"</td> <td>DN300</td> </tr> </tbody> </table>		Size		3/4"	DN20	1"	DN25	<b>2"</b>	<b>DN50</b>	3"	DN80	4"	DN100	6"	DN150	8"	DN200	10"	DN250	12"	DN300	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Primary Feature (Model)</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16</td> <td>A30</td> </tr> <tr> <td>Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16 PN25</td> <td>A71</td> </tr> <tr> <td>Automatic (Air-Release) Air Valve 1"; DN25, PN16 PN25 PN40 PN63</td> <td>A72</td> </tr> <tr> <td>Combination Air Valve 3/4"-3"; DN20-80, PN16</td> <td>C30</td> </tr> <tr> <td>Combination Air Valve 2"; DN50, PN16</td> <td>C35</td> </tr> <tr> <td>Combination Air Valve for Sewage &amp; Wastewater 2"-4"; DN50-100 PN10 PN16</td> <td>C50</td> </tr> <tr> <td><b>Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40</b></td> <td><b>C70</b></td> </tr> <tr> <td>Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40</td> <td>C72</td> </tr> <tr> <td>Combination Air Valve 3"-12"; DN80-300 PN16 PN25</td> <td>C75</td> </tr> <tr> <td>Combination Air Valve for Sewage &amp; Wastewater 3-4"; DN80-100 PN16 PN25</td> <td>C80</td> </tr> </tbody> </table>		Primary Feature (Model)	Code	Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16	A30	Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16 PN25	A71	Automatic (Air-Release) Air Valve 1"; DN25, PN16 PN25 PN40 PN63	A72	Combination Air Valve 3/4"-3"; DN20-80, PN16	C30	Combination Air Valve 2"; DN50, PN16	C35	Combination Air Valve for Sewage & Wastewater 2"-4"; DN50-100 PN10 PN16	C50	<b>Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40</b>	<b>C70</b>	Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40	C72	Combination Air Valve 3"-12"; DN80-300 PN16 PN25	C75	Combination Air Valve for Sewage & Wastewater 3-4"; DN80-100 PN16 PN25	C80	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Additional Features</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Without Additional Feature</td> <td>00</td> </tr> <tr> <td><b>Surge Protection (anti slam) (2"-C10/C30, C50, C70, C70, C75, C80)</b></td> <td><b>SP</b></td> </tr> <tr> <td>Assited Closing Surge Protection (C70 Down, Side and 2-4" PE Mushroom outlets, 2"-C10/C30, C50, C80)</td> <td>AC</td> </tr> <tr> <td>Inflow Prevention (2"-C10/C30-P, C50, C70 side outlet, C80)</td> <td>IP</td> </tr> </tbody> </table>		Additional Features	Code	Without Additional Feature	00	<b>Surge Protection (anti slam) (2"-C10/C30, C50, C70, C70, C75, C80)</b>	<b>SP</b>	Assited Closing Surge Protection (C70 Down, Side and 2-4" PE Mushroom outlets, 2"-C10/C30, C50, C80)	AC	Inflow Prevention (2"-C10/C30-P, C50, C70 side outlet, C80)	IP																																																										
Size																																																																																																																			
3/4"	DN20																																																																																																																		
1"	DN25																																																																																																																		
<b>2"</b>	<b>DN50</b>																																																																																																																		
3"	DN80																																																																																																																		
4"	DN100																																																																																																																		
6"	DN150																																																																																																																		
8"	DN200																																																																																																																		
10"	DN250																																																																																																																		
12"	DN300																																																																																																																		
Primary Feature (Model)	Code																																																																																																																		
Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16	A30																																																																																																																		
Automatic (Air-Release) Air Valve 3/4"-1"; DN20-25, PN16 PN25	A71																																																																																																																		
Automatic (Air-Release) Air Valve 1"; DN25, PN16 PN25 PN40 PN63	A72																																																																																																																		
Combination Air Valve 3/4"-3"; DN20-80, PN16	C30																																																																																																																		
Combination Air Valve 2"; DN50, PN16	C35																																																																																																																		
Combination Air Valve for Sewage & Wastewater 2"-4"; DN50-100 PN10 PN16	C50																																																																																																																		
<b>Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40</b>	<b>C70</b>																																																																																																																		
Combination Air Valve 2"-10"; DN50-250, PN16 PN25 PN40	C72																																																																																																																		
Combination Air Valve 3"-12"; DN80-300 PN16 PN25	C75																																																																																																																		
Combination Air Valve for Sewage & Wastewater 3-4"; DN80-100 PN16 PN25	C80																																																																																																																		
Additional Features	Code																																																																																																																		
Without Additional Feature	00																																																																																																																		
<b>Surge Protection (anti slam) (2"-C10/C30, C50, C70, C70, C75, C80)</b>	<b>SP</b>																																																																																																																		
Assited Closing Surge Protection (C70 Down, Side and 2-4" PE Mushroom outlets, 2"-C10/C30, C50, C80)	AC																																																																																																																		
Inflow Prevention (2"-C10/C30-P, C50, C70 side outlet, C80)	IP																																																																																																																		