



UL Product iQ
UL'S NEXT GENERATION CERTIFICATIONS SEARCH
The same trusted data in a modern search engine.

**NOW
AVAILABLE**

▶ LEARN MORE

HLCV.EX27641 Strainers, Pipeline

[Page Bottom](#)

Strainers, Pipeline

[See General Information for Strainers, Pipeline](#)

BERMAD UK LTD

EX27641

Unit 8 Hungerford Trading Estate
Smitham Bridge Rd
Hungerford Berkshire, RG17 0QP UNITED KINGDOM

Strainers, basket type, 3, 4, 5, 6, 8, 10 and 12 in. size, for rated working pressure of 200 psi, Model(s) 60F-01, Loss of head will approximate 3.2 psi for the 3 in. size at 346 GPM, 3.5 psi for the 4 in. size at 595 GPM, 3.6 psi for the 5 in. size at 937 GPM, 4.6 psi for the 6 in. size at 1350 GPM, 4.2 psi for the 8 in. size at 2375 GPM, 3.8 psi for the 10 in. size at 3750 GPM, 5.0 psi for the 12 in. size at 5233 GPM.

Strainers, pipe line Y type, grooved end, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated pressure of 175 psig, Model(s) 50F-01-VI

[Last Updated](#) on 2017-10-03

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".