

ELECTRICALLY CONTROLLED DELUGE VALVE WITH LOCAL RESET - 2-WAY SOV

Model FP-400E-2M

The BERMAD model 400E-2M is an elastomeric, hydraulic, line pressure operated deluge valve, designed specifically for advanced fire protection systems and the latest industry standards. The 400E-2M is activated by a 2-Way solenoid valve. Once open the 400E-2M latches open until locally reset.

The optional valve position indicator can include a limit switch suitable for Fire & Gas monitoring systems. The 400E-2M is ideal for systems with open nozzles for water or foam discharge and is available with electrical components to suit any hazardous location.



Features & Benefits

- Safety and reliability
 - Time proven, simple design with a fail safe actuation
 - Single piece rugged elastomer, VRSD technology
 - Obstacle-free, uninterrupted flow path
 - No mechanical moving parts
 - UL429A Listed 2-Way Solenoid Valve
 - Latches open: remains open until reset locally
- Quick and easy maintenance
 - Designed for high reliability and easy maintenance
 - In-line serviceable
 - Fast and easy cover removal

Approvals



UL-Listed
Special System Water Control
Valves, Deluge Type (VLFT)
Sizes 1½" - 10"



Det Norske Veritas
Type Approval
Sizes 1½" to 12"



ABS
American Bureau of Shipping
Type Approval
Sizes 1½" - 12"



Lloyd's Register
Type Approval
Sizes 1½" - 10"



Typical Applications

- Electric fire detection systems with control panels
- Automatic water spray systems
- Corrosive water systems
- Foam applications

Additional Features

- Valve position limit switches
- Seawater compatibility
- Alarm pressure switch
- Valve Position Indicator
- Corrosion resistant zinc based high build epoxy coating

Operation




The BERMAD model 400E-2M is held closed by water pressure in the control chamber [1]. Upon release of pressure from the control chamber, the valve opens.

Under NORMAL conditions, water pressure is supplied to the control chamber via the priming line [2] and strainer [3], and is then trapped in the control chamber by the check valve feature [4] of the easy-lock manual reset [5], the closed manual emergency release [6], and the closed solenoid valve [7]. The water pressure trapped in the control chamber of the deluge valve holds the diaphragm against the valve seat, sealing it drip-tight and keeping the system pipes dry.

Under FIRE conditions, water pressure is released from the control chamber, either with the manual emergency release, or by the solenoid switching to the release position in response to a signal from the heat detection system [E] by way of the fire & gas control system [C]. This opens the deluge valve allowing water to flow into the system piping and to the alarm devices. The 400E 2M latches open until reset locally by depressing the Easy-Lock button.

System P&ID



Components	
1	BERMAD 400E Deluge Valve
2	Priming Ball Valve
3	Priming Strainer
4	Check Valve
5	Easy-Lock – Manual Reset
6	Manual Emergency Release
7	2-Way Solenoid

Optional System Items	
ZS	Limit Switch Assembly
W	Water Motor Alarm
PS	Pressure Switch
I	Visual Valve Position indicator
PI	Pressure Gauge*
DV	Drain Valve*
DC	Automatic Drip Check Valve*
AV	3-way Alarm Test Valve*

* Included with suffix A in valve code (drain and indicating components)
See code designations and "factory supplied additional items" on page 4

System Installation

A typical installation of the BERMAD model 400E-2M, features automatic actuation by way of a 2-Way solenoid. It can also be triggered electrically by a signal from a fire & gas control system or an on-site emergency pushbutton. When open and fitted with a limit switch the valve can send a feedback signal to a remote valve status monitoring system.

Optional System Items



Water Motor Alarm



Exd Pressure
Switch - Stainless
Steel Enclosure for
Harsh
Environments




Single Ex d
Proximity S.S.316
Limit Switch



Pressure Gauge



Basket Strainer -
60F



Suggested Specifications

The deluge valve shall be UL-listed, 250 psi/17.2 bar rated.

The valve shall have an unobstructed flow path, with no stem guide or supporting ribs.

The deluge valve shall have no mechanical moving parts, and the actuation shall utilize a single-piece diaphragm assembly of VRSD technology.

The valve shall be coated internally and externally with UV protection. Optional: C5-VH grade of ISO-12944 standard against corrosive conditions.

The solenoid valve shall be a 2-way FM and UL429A-listed for 365 psi/25 bar with 65% of the rated voltage.

The control trim shall include a manual emergency release unit, an Easy-Lock latching valve, a Y-type strainer, two 4-inch pressure gauges, and an automatic drip-check with manual override.

A valve position indicator shall be provided, and equipped with two proximity limit switches.

Removing the valve cover for full inspection and maintenance shall be in-line, and not require removal of the valve from the pipeline.

The deluge valve and control trim shall be pre-assembled and hydraulically tested by a UL/FM and ISO 9000, 9001 certified factory.

Technical Data

Available Sizes:

Flanged- 1½, 2, 2½, 3, 4, 6, 8, 10 & 12"

Grooved- 2, 3, 4, 6, & 8"

Pressure Rating:



ANSI#150 - 17.2 bar | 250 psi

Grooved - 17.2 bar | 250 psi

Elastomer:

HTNR - Fabric Reinforced High Temperature

Compound - See engineering data



Valve Size	L #150 mm in	L Grooved mm in	A mm in	B mm in	C mm in	øD in	E mm in	F mm in	G mm in	Weight #150 kg lb
DN40 1½"	205 8.1	-	313 12.3	191 7.5	199 7.8	¾"	203 8.0	157 6.2	100 3.9	14 31
DN50 2"	205 8.1	205 8.1	313 12.3	191 7.5	199 7.8	1½"	203 8.0	157 6.2	100 3.9	15 33
DN65 2½"	205 8.1	-	325 12.8	196 7.7	253 10.0	1½"	205 8.1	157 6.2	74 2.9	17 37
DN80 3"	257 10.1	250 9.8	345 13.6	205 8.1	266 10.5	1½"	238 9.4	131 5.2	43 1.7	28 62
DN100 4"	320 12.6	320 12.6	328 12.9	212 8.3	316 12.4	1½"	258 10.2	99 3.9	43 1.7	40 88
DN150 6"	415 16.3	415 16.3	349 13.7	204 8.0	347 13.7	2"	334 13.1	52 2.0	-	84 185
DN200 8"	500 19.7	-	383 15.1	270 10.6	364 14.3	2"	385 15.2	9 0.4	-	147 323
DN250 10"	605 23.8	-	396 15.6	280 11.0	384 15.1	2"	382 15.0	-	-	162 356
DN300 12"	725 28.5	-	438 17.2	333 13.1	422 16.6	2"	513 20.2	-	-	242 532

IMPORTANT: Dimensions for the trim envelope or extents refer to a vertical orientation and may vary with specific component positioning - Apart from the "L" dimension, allow a tolerance of at least ±15%

Valve Code Designations

FP	6"	400E-2M	03	V	C	A5	ER	4DC	NN	N6nW																																																																																																																																																					
<table><tr><th>Category</th><th>Code</th></tr><tr><td>Standard</td><td>FP</td></tr><tr><td>Seawater</td><td>FS</td></tr><tr><td>Foam</td><td>FC</td></tr></table>	Category	Code	Standard	FP	Seawater	FS	Foam	FC	<table><tr><th>Valve Size</th><th></th></tr><tr><td>1½"</td><td>40 mm</td></tr><tr><td>2"</td><td>50 mm</td></tr><tr><td>2½"</td><td>60 mm</td></tr><tr><td>3"</td><td>80 mm</td></tr><tr><td>4"</td><td>100 mm</td></tr><tr><td>6"</td><td>150 mm</td></tr><tr><td>8"</td><td>200 mm</td></tr><tr><td>10"</td><td>250 mm</td></tr><tr><td>12"</td><td>300 mm</td></tr></table>	Valve Size		1½"	40 mm	2"	50 mm	2½"	60 mm	3"	80 mm	4"	100 mm	6"	150 mm	8"	200 mm	10"	250 mm	12"	300 mm	<table><tr><th>Installation</th><th>Code</th></tr><tr><td>Vertical</td><td>V</td></tr><tr><td>Horizontal</td><td>H</td></tr></table>	Installation	Code	Vertical	V	Horizontal	H	<table><tr><th>Material Body & Cover⁽¹⁾</th><th>Code</th></tr><tr><td>Ductile Iron A356⁽²⁾</td><td>C</td></tr><tr><td>Steel ASTM A216 WCB⁽²⁾</td><td>S</td></tr><tr><td>Stainless Steel 316</td><td>N</td></tr><tr><td>Nickel Al Bronze C95800</td><td>U</td></tr><tr><td>Super Duplex Grade 5A</td><td>D</td></tr></table>	Material Body & Cover ⁽¹⁾	Code	Ductile Iron A356 ⁽²⁾	C	Steel ASTM A216 WCB ⁽²⁾	S	Stainless Steel 316	N	Nickel Al Bronze C95800	U	Super Duplex Grade 5A	D	<table><tr><th>Coating</th><th>Code</th></tr><tr><td>High Build Epoxy</td><td>ER</td></tr><tr><td>Zinc Based High Build Epoxy⁽⁵⁾</td><td>ZR</td></tr><tr><td>Uncoated</td><td>UC</td></tr></table>	Coating	Code	High Build Epoxy	ER	Zinc Based High Build Epoxy ⁽⁵⁾	ZR	Uncoated	UC	<table><tr><th>Voltage - Main Valve N.O or N.C *</th><th>Code</th></tr><tr><td>24VDC - N.C.</td><td>4DC</td></tr><tr><td>24VDC - N.O.</td><td>4DO</td></tr><tr><td>110VDC - N.C.</td><td>5DC</td></tr><tr><td>110VDC - N.O.</td><td>5DO</td></tr><tr><td>110 - 120/AC - N.C.</td><td>5AC</td></tr><tr><td>110 - 120/AC - N.C.</td><td>5AO</td></tr><tr><td>220 - 240/AC - N.C.</td><td>2AC</td></tr><tr><td>221 - 240/AC - N.C.</td><td>2AO</td></tr></table>	Voltage - Main Valve N.O or N.C *	Code	24VDC - N.C.	4DC	24VDC - N.O.	4DO	110VDC - N.C.	5DC	110VDC - N.O.	5DO	110 - 120/AC - N.C.	5AC	110 - 120/AC - N.C.	5AO	220 - 240/AC - N.C.	2AC	221 - 240/AC - N.C.	2AO	<table><tr><th>End Connections</th><th>Code</th></tr><tr><td>ANSI#150RF</td><td>A5</td></tr><tr><td>ANSI#150FF</td><td>a5</td></tr><tr><td>ISO PN16</td><td>16</td></tr><tr><td>Grooved ANSI</td><td>VI</td></tr></table>	End Connections	Code	ANSI#150RF	A5	ANSI#150FF	a5	ISO PN16	16	Grooved ANSI	VI	<table><tr><th>Additional Feature</th><th>Code</th></tr><tr><td>Closing Speed Control</td><td>01</td></tr><tr><td>Opening Speed Control</td><td>02</td></tr><tr><td>Opening & Closing Speed Control</td><td>03</td></tr><tr><td>None</td><td>-</td></tr></table>	Additional Feature	Code	Closing Speed Control	01	Opening Speed Control	02	Opening & Closing Speed Control	03	None	-	<table><tr><th>Tubing & Fittings</th><th>Code</th></tr><tr><td>Stainless Steel 316</td><td>NN</td></tr><tr><td>Monel 400</td><td>MM</td></tr><tr><td>Super Duplex</td><td>DD</td></tr></table>	Tubing & Fittings	Code	Stainless Steel 316	NN	Monel 400	MM	Super Duplex	DD	<table><tr><th>Factory Supplied Additional Items</th><th>Code</th></tr><tr><td>General Purpose NEMA-4 Pressure Switch</td><td>P</td></tr><tr><td>Ex Proof NEC, Div.1 Pressure Switch⁽³⁾</td><td>P7</td></tr><tr><td>Ex d ATEX Pressure Switch⁽³⁾</td><td>P9</td></tr><tr><td>Ex d Pressure Switch, SS316 Enclosure⁽³⁾</td><td>P9Jn</td></tr><tr><td>Ex d Pressure Switch, SS316 Enclosure, Monel Sensor⁽³⁾</td><td>P9mJn</td></tr><tr><td>Single Limit Switch, General Purpose</td><td>S</td></tr><tr><td>Single Ex d Proximity limit Switch</td><td>S9</td></tr><tr><td>Double Ex d Proximity Limit Switch</td><td>SS9</td></tr><tr><td>Double Ex d Proximity Limit Switch with SS316 Junction Box</td><td>SS9Jn</td></tr><tr><td>Pressure Gauge Assembly⁽³⁾</td><td>6</td></tr><tr><td>S.S Glycerin Pressure Gauge Assembly⁽³⁾</td><td>6n</td></tr><tr><td>Monel Pressure Gauge Assembly⁽³⁾</td><td>6m</td></tr><tr><td>Ex Proof NEC Class 1 Div 1 Solenoid</td><td>7</td></tr><tr><td>Ex. d Atex Solenoid</td><td>9</td></tr><tr><td>Stainless steel 316 Solenoid Valve</td><td>K</td></tr><tr><td>Drain Valve</td><td>DV</td></tr><tr><td>Water Motor Alarm Assembly⁽³⁾</td><td>W</td></tr><tr><td>Special Elastomer</td><td>E</td></tr><tr><td>Large Control Filter</td><td>F</td></tr><tr><td>Valve Position Indicator</td><td>I</td></tr><tr><td>S.S 316 Trim Accessories</td><td>N</td></tr><tr><td>S.S Solenoid Valve</td><td>K</td></tr><tr><td>Pressure Transmitter⁽³⁾</td><td>Q</td></tr><tr><td>Drain and Indicating Components</td><td>A</td></tr></table>	Factory Supplied Additional Items	Code	General Purpose NEMA-4 Pressure Switch	P	Ex Proof NEC, Div.1 Pressure Switch ⁽³⁾	P7	Ex d ATEX Pressure Switch ⁽³⁾	P9	Ex d Pressure Switch, SS316 Enclosure ⁽³⁾	P9Jn	Ex d Pressure Switch, SS316 Enclosure, Monel Sensor ⁽³⁾	P9mJn	Single Limit Switch, General Purpose	S	Single Ex d Proximity limit Switch	S9	Double Ex d Proximity Limit Switch	SS9	Double Ex d Proximity Limit Switch with SS316 Junction Box	SS9Jn	Pressure Gauge Assembly ⁽³⁾	6	S.S Glycerin Pressure Gauge Assembly ⁽³⁾	6n	Monel Pressure Gauge Assembly ⁽³⁾	6m	Ex Proof NEC Class 1 Div 1 Solenoid	7	Ex. d Atex Solenoid	9	Stainless steel 316 Solenoid Valve	K	Drain Valve	DV	Water Motor Alarm Assembly ⁽³⁾	W	Special Elastomer	E	Large Control Filter	F	Valve Position Indicator	I	S.S 316 Trim Accessories	N	S.S Solenoid Valve	K	Pressure Transmitter ⁽³⁾	Q	Drain and Indicating Components	A
Category	Code																																																																																																																																																														
Standard	FP																																																																																																																																																														
Seawater	FS																																																																																																																																																														
Foam	FC																																																																																																																																																														
Valve Size																																																																																																																																																															
1½"	40 mm																																																																																																																																																														
2"	50 mm																																																																																																																																																														
2½"	60 mm																																																																																																																																																														
3"	80 mm																																																																																																																																																														
4"	100 mm																																																																																																																																																														
6"	150 mm																																																																																																																																																														
8"	200 mm																																																																																																																																																														
10"	250 mm																																																																																																																																																														
12"	300 mm																																																																																																																																																														
Installation	Code																																																																																																																																																														
Vertical	V																																																																																																																																																														
Horizontal	H																																																																																																																																																														
Material Body & Cover ⁽¹⁾	Code																																																																																																																																																														
Ductile Iron A356 ⁽²⁾	C																																																																																																																																																														
Steel ASTM A216 WCB ⁽²⁾	S																																																																																																																																																														
Stainless Steel 316	N																																																																																																																																																														
Nickel Al Bronze C95800	U																																																																																																																																																														
Super Duplex Grade 5A	D																																																																																																																																																														
Coating	Code																																																																																																																																																														
High Build Epoxy	ER																																																																																																																																																														
Zinc Based High Build Epoxy ⁽⁵⁾	ZR																																																																																																																																																														
Uncoated	UC																																																																																																																																																														
Voltage - Main Valve N.O or N.C *	Code																																																																																																																																																														
24VDC - N.C.	4DC																																																																																																																																																														
24VDC - N.O.	4DO																																																																																																																																																														
110VDC - N.C.	5DC																																																																																																																																																														
110VDC - N.O.	5DO																																																																																																																																																														
110 - 120/AC - N.C.	5AC																																																																																																																																																														
110 - 120/AC - N.C.	5AO																																																																																																																																																														
220 - 240/AC - N.C.	2AC																																																																																																																																																														
221 - 240/AC - N.C.	2AO																																																																																																																																																														
End Connections	Code																																																																																																																																																														
ANSI#150RF	A5																																																																																																																																																														
ANSI#150FF	a5																																																																																																																																																														
ISO PN16	16																																																																																																																																																														
Grooved ANSI	VI																																																																																																																																																														
Additional Feature	Code																																																																																																																																																														
Closing Speed Control	01																																																																																																																																																														
Opening Speed Control	02																																																																																																																																																														
Opening & Closing Speed Control	03																																																																																																																																																														
None	-																																																																																																																																																														
Tubing & Fittings	Code																																																																																																																																																														
Stainless Steel 316	NN																																																																																																																																																														
Monel 400	MM																																																																																																																																																														
Super Duplex	DD																																																																																																																																																														
Factory Supplied Additional Items	Code																																																																																																																																																														
General Purpose NEMA-4 Pressure Switch	P																																																																																																																																																														
Ex Proof NEC, Div.1 Pressure Switch ⁽³⁾	P7																																																																																																																																																														
Ex d ATEX Pressure Switch ⁽³⁾	P9																																																																																																																																																														
Ex d Pressure Switch, SS316 Enclosure ⁽³⁾	P9Jn																																																																																																																																																														
Ex d Pressure Switch, SS316 Enclosure, Monel Sensor ⁽³⁾	P9mJn																																																																																																																																																														
Single Limit Switch, General Purpose	S																																																																																																																																																														
Single Ex d Proximity limit Switch	S9																																																																																																																																																														
Double Ex d Proximity Limit Switch	SS9																																																																																																																																																														
Double Ex d Proximity Limit Switch with SS316 Junction Box	SS9Jn																																																																																																																																																														
Pressure Gauge Assembly ⁽³⁾	6																																																																																																																																																														
S.S Glycerin Pressure Gauge Assembly ⁽³⁾	6n																																																																																																																																																														
Monel Pressure Gauge Assembly ⁽³⁾	6m																																																																																																																																																														
Ex Proof NEC Class 1 Div 1 Solenoid	7																																																																																																																																																														
Ex. d Atex Solenoid	9																																																																																																																																																														
Stainless steel 316 Solenoid Valve	K																																																																																																																																																														
Drain Valve	DV																																																																																																																																																														
Water Motor Alarm Assembly ⁽³⁾	W																																																																																																																																																														
Special Elastomer	E																																																																																																																																																														
Large Control Filter	F																																																																																																																																																														
Valve Position Indicator	I																																																																																																																																																														
S.S 316 Trim Accessories	N																																																																																																																																																														
S.S Solenoid Valve	K																																																																																																																																																														
Pressure Transmitter ⁽³⁾	Q																																																																																																																																																														
Drain and Indicating Components	A																																																																																																																																																														

Notes:

(1) Other materials available see engineering data

(2) Coated internally and externally

(3) Supplied loose

(4) Consult BERMAD for availability

(5) For valves up to and including 10"

Notes:

- (1) Other materials available see engineering data
- (2) Coated internally and externally
- (3) Supplied loose
- (4) Consult BERMAD for availability
- (5) For valves up to and including 10"

* NO or NC refers to the main valve status when the Solenoid is de-energized

*More options available – consult BERMAD