HYDRAULICALLY CONTROLLED ANTI-COLUMNING DELUGE VALVE WITH LOCAL RESET

Model FP-400Y-5M

The BERMAD model 400Y-5M is an elastomeric, hydraulic, line pressure operated deluge valve, designed specifically for advanced fire protection systems and the latest industry standards.
The 400Y-5M is activated by a pressure operated relay valve, which latches the main valve open until locally reset. The 400Y-5M is ideal for systems with remote or elevated wet pilot lines, due to its boosted local pressure release. The optional valve position indicator can include a limit switch suitable for Fire & Gas monitoring systems.



Features & Benefits

- Safety and reliability
  - Time proven, simple design with a fail safe actuation
  - Single piece rugged elastomer, VRSD technology
  - No mechanical moving parts
  - Latches open: remains open until reset locally
  - Valve position limit switches (optional)
  - Local valve position indicator beacon (optional)
- High performance
  - Very high flow efficiency
  - Straight through Y type body
  - Approved for PN25 / 365 psi
- Specifically-designed for fire protection
  - Face-to-face length standardized to ISO 5752 EN 558-1
  - Meets the requirements of the industry standards
  - Designed for high reliability and easy maintenance
  - Quick opening for long pilot lines
- Quick and easy maintenance
  - In-line serviceable
  - Fast and easy cover removal
  - Swivel mounted drain valves (for valves 3" and larger)

Approvals

c UL us LISTED	UL-Listed Special System Water Control Valves, Deluge Type (VLFT) Sizes 1½" - 16"
FM APPROVED	FM Approved for Deluge Sprinkler Systems Sizes 1½" - 8"
DNV	Det Norske Veritas Type Approval Sizes 1½" to 16"
ABS TYPE APPROVED PRODUCT	ABS American Bureau of Shipping Type Approval Sizes 1½" - 12"
Lloyd's Register TA TYPE APPROVED	Lloyd's Register Type Approval Sizes 1½" - 10"

Typical Applications


- Remote or elevated wet pilot lines
- Automatic water spray systems
- Hydraulic remote controlled systems
- Foam applications

Additional Features


- Valve position limit switches
- Local valve position indicator beacon
- Alarm pressure switch
- Water motor alarm
- Seawater compatibility
- Drain valve/s inlet/outlet

All images in this catalog are for illustration only

Operation




Valve Closed (normal conditions)


Valve Open (fire conditions)

The BERMAD model 400Y-5M is held closed by water pressure in the control chamber [1]. Upon release of pressure from the control chamber, the valve opens.
Under NORMAL conditions, water pressure is supplied to the control chamber via the priming line [2] and strainer [3],and a restriction orifice [5] and then trapped in the control chamber by a check valve [4], a manual emergency release [6], and a relay valve (URV-M) [7] that is held closed by hydraulic pilot line pressure [E]. The water pressure trapped in the control chamber holds the diaphragm against the valve seat, sealing it drip-tight and keeping the system pipes dry.
Under FIRE conditions, water pressure is released from the control chamber, either with the manual emergency release, or by the URV-M opening automatically in response to a decrease in hydraulic pilot-line pressure. This latches the 400Y-5M deluge valve open, allowing water to flow into the system piping and to the alarm device [9]. The URV-M is factory set to operate with a minimum pilot line elevation of 10 meters above the valve. Additional spring tension can be set to suit greater elevations, up to a maximum of 70 meters above the valve (refer to the Valve Code Designation on the last page).

System P&ID



	Components
1	BERMAD 400Y Deluge Valve
2	Priming Ball Valve
3	Priming Strainer
4	Check Valve
5	Restriction Orifice
6	Manual Emergency Release
7	URV-2-M Relay Valve

	Optional System Items
I	Visual Valve Position indicator
PS	Pressure Switch
W	Water Motor Alarm
ZS	Limit Switch Assembly
DV2	Downstream Drain valve
DV	Drain Valve*
PI	Pressure Gauge*
AV	3-way Alarm Test Valve*
DC	Automatic Drip Check Valve*

** Included with suffix A in valve code and mandatory for FM approval (drain and indicating components) See code designations on page 4 "Factory Supplied Additional Items"*

System Installation

A typical installation of the BERMAD model 400Y-5M features automatic actuation via a pressure operated relay valve, triggered by a wet pilot line with closed fusible plugs elevated above the deluge valve. When open and fitted with a limit switch, the valve sends a feedback signal to the remote valve position monitoring system.

Optional System Items



Pressure Gauge




Pressure Switch



Visual Position Indicator



Rotating Limit Switch Box



Suggested Specifications

The deluge valve shall be UL-listed and FM-approved, 365-psi/25-bar rated, with a straight-through Ytypebody.
The valve shall have an unobstructed flow path, with no stem guide or supporting ribs.
The deluge valve shall have no mechanical moving parts, and the actuation shall utilize a single-piece diaphragm assembly of VRSD technology.
The valve shall be coated internally and externally with UV protection. Optional: C5-VH grade of ISO-12944 standard against corrosive conditions.
The control trim shall include an auxiliary latching relay valve, a manual emergency release unit, a Y-type strainer, two 4-inch pressure gauges, an automatic drip-check with manual override, and a ball drain valve with a 360 degree swivel.
A valve position indicator shall be provided, and equipped with two proximity limit switches.
Removing the valve cover for full inspection and maintenance shall be in-line and not require removal of the control trim.
The deluge valve and control trim shall be pre-assembled and hydraulically tested by a UL/FM and ISO 9000, 9001 certified factory.


All images in this catalog are for illustration only


Technical Data

Available Sizes:
Flanged- 1½, 2, 2½, 3, 4, 6, 8, 10, 12, 14 & 16"
Grooved- 1½, 2, 2½, 3, 4, 6, 8 & 10"

Pressure Rating:
ANSI#150 - 17.2 bar
ANSI#300 - 1½" to 10" - 25 bar
ANSI#300 - 12" to 16" - 20 bar
Grooved - 17.2 / 25 bar

Elastomer:
HTNR - Fabric Reinforced High Temperature Compound - See engineering data





Valve Size	L #150 (mm)	L Grooved (mm)	L #300 (mm)	A (mm)	B (mm)	C (mm)	øD(in)	E (mm)	F (mm)	G (mm)	Weight #150 (Kg)	Weight #300 (Kg)
DN40 | 1½"	230	230	230	293	200	177	¾"	215	151	178	18	20
DN50 | 2"	230	230	238	293	200	177	¾"	215	151	178	19	21
DN65 | 2½"	235	235	241	296	200	183	1½"	215	148	157	22	24
DN80 | 3"	310	310	326	313	259	221	1½"	186	82	88	36	41
DN100 | 4"	350	320	368	343	268	287	2"	199	55	135	50	57
DN150 | 6"	480	480	506	358	321	302	2"	234	-	27	97	117
DN200 | 8"	600	600	626	392	380	317	2"	301	-	2	167	187
DN250 | 10"	730	730	730	406	380	317	2"	301	-	-	200	235
DN300 | 12"	850	-	888	478	463	380	2"	441	-	-	357	406
DN350 | 14"	980	-	980	478	463	379	2"	441	-	-	393	463
DN400 | 16"	1100	-	1100	478	463	405	2"	417	-	-	444	564

IMPORTANT: Dimensions for the trim envelope or extents refer to a vertical orientation and may vary with specific component positioning -Apart from the "L" dimension, allow a tolerance of at least ±15%

Valve Code Designations

FP | 6" | 400Y-5M | M6 | 03 | V | C | A5 | ER | NN | N6nW

Category	Code
Standard	FP
Seawater	FS
Foam	FC

Pilot Line Trip Point	Code
Elevation below 10m/33ft	00
Max elevation 35m/115ft (7)	M6
Max elevation 70m/230ft (8)	M7

Valve Size	
1½"	40 mm
2"	50 mm
2½"	65 mm (6)
3"	80 mm
4"	100 mm
6"	150 mm
8"	200 mm
10"	250 mm
12"	300 mm
14"	350 mm
16"	400 mm

Additional Feature	Code
Closing Speed Control	01
Opening Speed Control	02
Opening & Closing	03
None	-

Installation	Code
Vertical	V
Horizontal	H

End Connection	Code
ANSI#150RF	A5
ANSI#150FF	a5
ANSI#300RF	A3
ANSI#300FF	a3
ISO PN16	16
ISO PN25	25
Grooved 17.2 bar / 250 psi (5)	VI
Grooved 25 bar / 365 psi (5)	V2

Coating	Code
High Build Epoxy	ER
Zinc Based High Build Epoxy (5)	ZR
Uncoated	UC

Material Body & Cover (1)	Code
Ductile Iron A356 (2)	C
Steel ASTM A216 WCB (2)	S
Stainless Steel 316	N
Nickel Al Bronze C95800	U
Super Duplex Grade 5A	D

Tubing & Fittings	Code
Stainless Steel 316	NN
Monel 400	MM
Super Duplex	DD

Factory Supplied Additional Items*	Code
General Purpose NEMA-4 Pressure Switch	P
Ex Proof NEC, Div.1 Pressure Switch (3)	P7
Ex d ATEX Pressure Switch (3)	P9
Ex d Pressure Switch, SS316 Enclosure (3)	P9Jn
Ex d Pressure Switch, SS316 Enclosure, Monel Sensor (3)	P9mJn
Single Limit Switch, General Purpose	S
Single Ex d Proximity limit Switch	S9
Double Ex d Proximity Limit Switch	SS9
Double Ex d Proximity Limit Switch with SS316 Junction Box	SS9Jn
Pressure Gauge Assembly (3)	6
S.S Glycerin Pressure Gauge Assembly (3)	6n
Monel Pressure Gauge Assembly (3)	6m
Stainless steel 316 Solenoid Valve	K
Drain Valve	DV
Water Motor Alarm Assembly (3)	W
Special Elastomer (4)	E
Large Control Filter	F
Valve Position Indicator	I
S.S 316 Trim Accessories	N
Pressure Transmitter (3)	Q
Drain and Indicating Components	A

*More options available – consult BERMAD

Notes:
(1) Other materials available see engineering data
(2) Coated internally and externally
(3) Supplied loose
(4) Consult BERMAD for availability
(5) For valves up to and including 10"
(6) Available in Ductile Iron only
(7) Minimum supply pressure to the Deluge Valve shall be at least 5.0 barg
(8) Minimum supply pressure to the Deluge Valve shall be at least 8.5 barg

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.
© Copyright 2015-2025 BERMAD CS Ltd