

LARGE CONTROL FILTER

Model F

The Large Control Filter has a high capacity and a large screening area. It is used where control fluid might be dirtier than usual, and the standard control filter would be inadequate.

Added advantages include, increasing the maintenance interval and the valve system reliability and helping to prevent false operation of deluge systems that might occur due to a clogged control priming line.

Standard Construction

- Body: Carbon Steel, Red Epoxy coated
- Covers: Brass
- Stem & Nut: Stainless Steel 304
- Screen: SS 316L-50 mesh, 300 µm
- Gaskets: NBR O-rings

Stainless Steel Construction

- Body: Stainless Steel 316
- Covers: Stainless Steel 316
- Stem & Nut: Stainless Steel 316
- Screen: SS 316L-50 mesh, 300 µm
- Gaskets: NBR O-rings

NAB Construction

- Body: Ni-Al-Bronze
- Covers: Ni-Al-Bronze
- Stem: Ni-Al-Bronze
- Nut (dry): Stainless Steel 316
- Screen: Polyethylene, 50 mesh, 300 µm
- Gaskets: NBR O-rings

Temperature Rating

Water: 80°C / 180°F

Pressure Rating

25 bar / 365 psi

Connections

3/8" NPT (F)

Weight

2.7kg / 6lbs

