



IR

3"x3"

350-55

A

P

P

VI

UC

4AC

PP

Z

Size

2"x2"	DN50x50
3"x3"	DN80x80
3"x3/2" ⁽¹⁾	DN80x80/50
4"x4"	DN100x100
4"x4/3" ⁽²⁾	DN100x100

(1) ■ Straight flow only
■ Port 1 (drain) is 3" grooved and 2" female threaded
(2) ■ Straight flow only
■ Port 1 (drain) is 4" grooved and 3" female threaded

Port 1 (Lower Seat) Connection

Code
BSP Threaded Female
Grooved
"Havazelet" (4"x4" Only)

Port 2 / C Connections

Code
Grooved ANSI C 606-81 Steel Pipe
BSP Threaded Female 2"x2" only

Optional 2" Adaptors are available on request:
■ BSP Male Threaded x Grooved (when Grooved is required).
■ BSP Male Threaded x NPT Female Threaded (when NPT is required).

Coating

Code
Uncoated

Voltage-Main Valve Position (When Solenoid De-Energized)

Code
24VAC - Normally Open
24VDC - Normally Open
12VDC - Normally Open
12VDC - Latch Solenoid S-985 (3 Leads)
12VDC - Latch Solenoid S-982 (2 Leads)
9VDC - Latch Solenoid

Other electrical ratings available on request.

Primary Features

Code
Filter Backwash Valve
Filter Backwash Valve with Hydraulic Accelerator
Filter Backwash Valve, Solenoid Controlled

Other primary features available on request.

Tubing & Fittings

Code
Plastic Tubing & Fittings

Pattern / Flow Options

Code
Angle Flow
Straight Flow
Angle & Reverse Flow
Straight & Reverse Flow

Body Material

Code
Nylon - G.F.

Voltage-Main Valve Position (When Solenoid De-Energized)

Code
24VAC - Normally Open
24VDC - Normally Open
12VDC - Normally Open
12VDC - Latch Solenoid S-985 (3 Leads)
12VDC - Latch Solenoid S-982 (2 Leads)
9VDC - Latch Solenoid

Other electrical ratings available on request.

Additional Attributes Unlimited Selection

Code
EPDM Elastomers Seals & Diaphragm
Viton Elastomers Seals & Diaphragm
Metal Control Accessories
Stainless Steel 316 Seat & Shaft
Manual Selector
Plastic Gauge Test Point

Other additional attributes are optional.