



PRESSURE REDUCING HYDROMETER, HYDRAULIC CONTROLLED

Model IR-920-M0-50-3W-KXZ

The BERMAD Pressure Reducing Hydrometer with manual selector and hydraulic remote control combines a Woltman-type turbine water meter with a hydraulically operated, diaphragm-actuated control valve. Functioning as both a mainline flow meter and a Pressure Reducing valve, it reduces higher upstream pressure to a lower constant downstream pressure or opens fully when line pressure drops below settings. The Hydrometer features a vacuum-sealed register for precise volume measurement. An optional pulse output enhances system capabilities.



[1] BERMAD Model IR-920-M0-50-3W-KXZ opens upon pressure drop command, establishes reduced pressure zone, and measures flow.

Features & Benefits


- Integrated "All-in-One" Control Valve & Flow Meter
 - Saves space, cost and maintenance
- Line Pressure Driven, Hydraulically Controlled On/Off
 - Protects downstream systems
 - Opens fully upon line pressure drop
- Magnetic Drive with Vacuum-Sealed Register
 - Water-free gear train mechanism
 - Reed-switch tension free pulse output
 - Various pulse combinations
- Internal Inlet & Outlet Flow Straighteners
 - Saves on straightening distances
 - Maintains accuracy
- Integrated Flow Metering Calibration Device
 - Precise measurement
- User-Friendly Design
 - Easy pressure setting
 - Simple in-line inspection and service

Typical Applications

- Automated Irrigation Systems
- Remote Flow Data Read-Out
- Flow Monitoring & Leakage Control
- Pressure Reducing Systems
- Systems Subject to Varying Supply Pressure
- Distribution Centers
- Volumetric Irrigation Systems

Operation:

The Shuttle Valve [1] hydraulically connects the Pressure Reducing Pilot (PRP) [2] to the Control Chamber [3] of the Hydrometer through the Manual Selector [4]. The PRP commands the Hydrometer to throttle closed when Downstream Pressure [P2] rises above setting and to open fully when it drops. Upon pressure rise command, the Shuttle Valve switches automatically, pressurizing the control chamber and closing the Hydrometer. The Manual Selector [4] enables local closing.





IR-920-M0-50-3W-KXZ

Technical Data

Pressure Rating:
10 bar

Operating Pressure Range:
0.5-10 bar

Materials

Body & Cover: Ductile Iron
Diaphragm: NR, Nylon fabric reinforced
Seals: NR, Nylon fabric reinforced
Spring: Stainless Steel
Internals: Stainless Steel & Plastic Reinforced Nylon
Impeller: Polypropylene
Pivots and Bearings: Polypropylene
**Other materials are available on request*

Control Loop Accessories

PR Pilot: PC-SHARP-X-P


Spring	Spring Color	Setting range
J	Green	0.2-1.7 bar
K	Gray	0.5-3.0 bar
N	Natural	0.8-6.5 bar
V	Blue & White	1.0-10.0 bar

Standard spring - marked in bold

Tubing and Fittings:
Polyethylene and Polypropylene

Technical Specifications

For other patterns and end connection types,
Please refer to [BERMAD](#) full engineering page.



Size	Pattern	End Connection	Weight (Kg)	L (mm)	H (mm)	h (mm)	W	CCDV (Lit)	KV
1½" ; DN40	Globe	Threaded	7.2	250	270	95	143	0.16	41
2" ; DN50	Globe	Threaded	7.3	250	277	95	143	0.16	46
2" ; DN50	Angle 90°	Threaded	8.1	120	353	155	143	0.16	51
3"R ; DN80R	Globe	Threaded	7.3	250	277	79	143	0.16	50
3"R ; DN80R	Globe	Flanged	16	310	298	100	200	0.16	50
3" ; DN80	Globe	Flanged	23	300	382	123	210	0.49	115
3" ; DN80	Angle 90°	Flanged	25.8	150	402	196	210	0.49	126
4" ; DN100	Globe	Flanged	31	350	447	137	250	1	147
4" ; DN100	Angle 90°	Flanged	36.1	180	481	225	250	1	180

CCDV = Control Chamber Displacement Volume • **Threaded** = BSP & NPT are available.

• Extra length for male Threaded: 1½" Globe= 67(mm) ; 2" Globe & Angle= 77(mm)

Flow Properties

Size	Accuracy	DN40	DN50	DN80R	DN80	DN100
Q @ (m³/h)		1½"	2"	3"R	3"	4"
Q1 Minimum Flow	±5%	0.8	0.8	1.2	1.2	1.8
Q2 Transitional Flow	±2%	1.3	1.3	3	3	4.5
Q3 Permanent Flow	±2%	25	40	100	100	160
Q4 Maximum Flow (Short Time)	±2%	31	50	125	125	200

*ISO 4604

Pulse Option


Register Type	Reed Switch - Single		Reed Switch - Combined		Electronic					
	One pulse per		One pulse per		One pulse per					
Size	10L	100L	1m³	10m³	10L+100L	1m³+10m³	10L	100L	1m³	10m³
1½"-4" ; DN40-100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

- 10L pulse (only available with electronic register) suitable for flows up to 180 m³/h.
- Two parallel pulses are transmitted. other pulse rates are available on request.

Additional Features

Code	Description
ME	Electronic register (upgrade kit is available)

Flow Chart



Differential Pressure & Flow Calculation

$$\Delta P = \left(\frac{Q}{Kv} \right)^2$$

$Kv = m^3/h @ \Delta P \text{ of } 1 \text{ bar}$
 $Q = m^3/h$
 $\Delta P = \text{bar}$