
PRESSURE REDUCING HYDROMETER

Model IR-920-M0-2W-R

The BERMAD Pressure Reducing Hydrometer combines a Woltman-type turbine water meter and a hydraulically operated, diaphragm-actuated control valve. It functions as both a mainline flow meter and a pressure-reducing valve, reducing higher upstream pressure to a constant downstream pressure and modulating open if line pressure drops below the setting. The Hydrometer features a magnetically coupled, vacuum-sealed register for precise volume measurement. An optional pulse output enhances system capabilities.





- [1] BERMAD Model IR-920-M0-2W-R protects the system measures the flow.
- [2] BERMAD Relief Valve Model IR-43Q-2W-R

Features & Benefits


- Integrated "All-in-One" Control Valve & Flow Meter
 - Saves space, cost and maintenance
- Hydraulic Pressure Control
 - Line pressure driven
 - Protects downstream
- Magnetic Drive with Vacuum-Sealed Register
 - Water-free gear train mechanism
 - Reed-switch tension free pulse output
 - Various pulse combinations
- Internal Inlet & Outlet Flow Straighteners
 - Saves on straightening distances
 - Maintains accuracy
- Integrated Flow Metering Calibration Device
 - Precise measurement
- User-Friendly Design
 - Easy pressure setting
 - Simple in-line inspection and service
 - Easy addition of control features

Typical Applications

- Automated Irrigation Systems
- Pressure Reducing Systems
- Remote Flow Data Read-Out
- Flow Monitoring & Leakage Control
- Volumetric Irrigation Systems

Operation:

The Pressure Reducing Pilot (PRP) [1] commands the Hydrometer to throttle-closed when Downstream Pressure [P2] rises above pilot setting, and to modulate open when it drops below pilot setting. The downstream Cock Valve [2] enables manual closing.



Technical Data

Pressure Rating:

16 bar

Operating Pressure Range:

0.5-16 bar

Materials

Body & Cover: Ductile Iron Diaphragm: NR, Nylon fabric

reinforced

Seals: NR, Nylon fabric reinforced

Spring: Stainless Steel

Internals: Stainless Steel & Plastic

Reinforced Nylon Impeller: Polypropylene Pivots and Bearings:

Polypropylene

*Other materials are available on

request

Technical Specifications


For other patterns and end connection types, Please refer to **BERMAD** full engineering page.

Control Loop Accessories

PR Pilot: PC-20-A-MP

Spring	Spring Color	Setting range			
N	Natural	0.8-6.5 bar			
V	Blue & White	1.0-10.0 bar			
Standard spring - marked in bold					

Tubing and Fittings: Reinforced Nylon and Brass



Size	Pattern	End Connection	Weight (Kg)	L (mm)	H (mm)	h (mm)	W	CCDV (Lit)	KV
1½" ; DN40	Globe	Threaded	7.2	250	270	95	143	0.16	41
2" ; DN50	Globe	Threaded	7.3	250	277	95	143	0.16	46
2" ; DN50	Angle 90°	Threaded	8.1	120	353	155	143	0.16	51
3"R ; DN80R	Globe	Threaded	7.3	250	277	79	143	0.16	50
3"R ; DN80R	Globe	Flanged	16	310	298	100	200	0.16	50
3" ; DN80	Globe	Flanged	23	300	382	123	210	0.49	115
3"; DN80	Angle 90°	Flanged	25.8	150	402	196	210	0.49	126
4"; DN100	Globe	Flanged	31	350	447	137	250	1	147
4"; DN100	Angle 90°	Flanged	36.1	180	481	225	250	1	180
6"; DN150	Globe	Flanged	71	500	602	216	380	3.8	430
6" ; DN150	Angle 90°	Flanged	76.7	250	585	306	380	3.8	473
8"; DN200	Globe	Flanged	93	600	617	228	380	3.8	550
8"; DN200	Angle 90°	Flanged	82.5	250	585	280	380	3.8	605

CCDV = Control Chamber Displacement Volume • Threaded = BSP & NPT are available.

Flow Properties

Size	Accuracy	DN40	DN50	DN80R	DN80	DN100	DN150	DN200
Q @ (m³/h)		11/2"	2"	3"R	3"	4"	6"	8"
Q1 Minimum Flow	±5%	0.8	0.8	1.2	1.2	1.8	4	6.3
Q2 Transitional Flow	±2%	1.3	1.3	3	3	4.5	10	15.8
Q3 Permanent Flow	±2%	25	40	100	100	160	250	400
Q4 Maximum Flow (Short Time)	±2%	31	50	125	125	200	313	500

^{*}ISO 4604

Pulse Option

Register Type	Reed Switch - Single			ngle	Reed Switch	Electronic				
Size	One pulse per		One pulse per		One pulse per					
3126	10L	100L	1m³	10m³	10L+100L	1m³+10m³	10L	100L	1m³	10m³
1½"-4"; DN40-100		✓	✓		✓		✓	✓	✓	
6"-10" : DN150-250			1	1		1		1	1	1


- 10L pulse (only available with electronic register) suitable for flows up to 180 m³/h.
- Two parllel pulses are transmitted. other pulse rates are avaiable on reauest.

Additional Features

Code	Description
ME	Electronic register (upgrade kit is available)

Flow Chart

2-Way circuit "Added Head Loss" (for "V" below 2 m/s): 0.3 bar



Differential Pressure & Flow Calculation

$$\Delta P = \left(\frac{Q}{Kv}\right)^{2}$$

$$Kv = m^{3}/h \otimes \Delta P \text{ of 1 bar}$$

$$Q = m^{3}/h$$

$$\Delta P = bar$$



www.bermad.com

[•] Extra length for male Threaded: 11/2" Globe= 67(mm); 2" Globe & Angle= 77(mm)