



IR	2"	C10	SP	P	S	BP	EV	T																																																																
<table border="1"> <thead> <tr> <th>Sector</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Irrigation</td> <td>IR</td> </tr> </tbody> </table>		Sector	Code	Irrigation	IR	<table border="1"> <thead> <tr> <th>Body Material</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Plastic</td> <td>P</td> </tr> <tr> <td>Ductile Iron</td> <td>C</td> </tr> <tr> <td>Stainless Steel</td> <td>N</td> </tr> <tr> <td>Ductile Iron & Composite</td> <td>J</td> </tr> <tr> <td>Stainless Steel & Composite</td> <td>G</td> </tr> </tbody> </table>		Body Material	Code	Plastic	P	Ductile Iron	C	Stainless Steel	N	Ductile Iron & Composite	J	Stainless Steel & Composite	G	<table border="1"> <thead> <tr> <th>Coating (For Ductile Iron Only)</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Epoxy UV Protected Blue</td> <td>EV</td> </tr> </tbody> </table>		Coating (For Ductile Iron Only)	Code	Epoxy UV Protected Blue	EV																																															
Sector	Code																																																																							
Irrigation	IR																																																																							
Body Material	Code																																																																							
Plastic	P																																																																							
Ductile Iron	C																																																																							
Stainless Steel	N																																																																							
Ductile Iron & Composite	J																																																																							
Stainless Steel & Composite	G																																																																							
Coating (For Ductile Iron Only)	Code																																																																							
Epoxy UV Protected Blue	EV																																																																							
<table border="1"> <thead> <tr> <th>Size</th> <th></th> </tr> </thead> <tbody> <tr> <td>1/2"</td> <td>DN12</td> </tr> <tr> <td>3/4"</td> <td>DN20</td> </tr> <tr> <td>1"</td> <td>DN25</td> </tr> <tr> <td>2"</td> <td>DN50</td> </tr> <tr> <td>3"</td> <td>DN80</td> </tr> <tr> <td>4"</td> <td>DN100</td> </tr> <tr> <td>6"</td> <td>DN150</td> </tr> <tr> <td>8"</td> <td>DN200</td> </tr> <tr> <td>10"</td> <td>DN250</td> </tr> <tr> <td>12"</td> <td>DN300</td> </tr> </tbody> </table>		Size		1/2"	DN12	3/4"	DN20	1"	DN25	2"	DN50	3"	DN80	4"	DN100	6"	DN150	8"	DN200	10"	DN250	12"	DN300	<table border="1"> <thead> <tr> <th>Outlet Types</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Side</td> <td>S</td> </tr> <tr> <td>Down (C50, C70, C75)</td> <td>D</td> </tr> <tr> <td>Mushroom (C70, C75)</td> <td>M</td> </tr> </tbody> </table>		Outlet Types	Code	Side	S	Down (C50, C70, C75)	D	Mushroom (C70, C75)	M																																							
Size																																																																								
1/2"	DN12																																																																							
3/4"	DN20																																																																							
1"	DN25																																																																							
2"	DN50																																																																							
3"	DN80																																																																							
4"	DN100																																																																							
6"	DN150																																																																							
8"	DN200																																																																							
10"	DN250																																																																							
12"	DN300																																																																							
Outlet Types	Code																																																																							
Side	S																																																																							
Down (C50, C70, C75)	D																																																																							
Mushroom (C70, C75)	M																																																																							
<table border="1"> <thead> <tr> <th>Primary Feature (Model)</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Vacuum Breaker 1/2"; DN12 PN10</td> <td>ARV</td> </tr> <tr> <td>Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN10</td> <td>A10</td> </tr> <tr> <td>Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN16</td> <td>A30</td> </tr> <tr> <td>Kinetic (Air-Vacuum) Air Valve 3/4"-2"; DN20-50, PN10</td> <td>K10</td> </tr> <tr> <td>Combination Air Valve 3/4"-3"; DN20-80, PN10</td> <td>C10</td> </tr> <tr> <td>Combination Air Valve 2"; DN50, PN10</td> <td>C15</td> </tr> <tr> <td>Combination Air Valve 3/4"-3"; DN20-80, PN16</td> <td>C30</td> </tr> <tr> <td>Combination Air Valve 2"; DN50, PN16</td> <td>C35</td> </tr> <tr> <td>Combination Air Valve for Sewage & Wastewater 2"-4"; DN50-100, PN10 PN16</td> <td>C50</td> </tr> <tr> <td>Combination Air Valve - Metal 2"-10"; DN50-250, PN16 PN25 PN40</td> <td>C70</td> </tr> <tr> <td>Combination Air Valve - Metal 3"-12"; DN80-300, PN16 PN25 PN40</td> <td>C75</td> </tr> </tbody> </table>		Primary Feature (Model)	Code	Vacuum Breaker 1/2"; DN12 PN10	ARV	Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN10	A10	Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN16	A30	Kinetic (Air-Vacuum) Air Valve 3/4"-2"; DN20-50, PN10	K10	Combination Air Valve 3/4"-3"; DN20-80, PN10	C10	Combination Air Valve 2"; DN50, PN10	C15	Combination Air Valve 3/4"-3"; DN20-80, PN16	C30	Combination Air Valve 2"; DN50, PN16	C35	Combination Air Valve for Sewage & Wastewater 2"-4"; DN50-100, PN10 PN16	C50	Combination Air Valve - Metal 2"-10"; DN50-250, PN16 PN25 PN40	C70	Combination Air Valve - Metal 3"-12"; DN80-300, PN16 PN25 PN40	C75	<table border="1"> <thead> <tr> <th>End Connections / Pressure Ratings</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td rowspan="4">Threaded</td> <td>BSP Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)</td> <td>BP</td> </tr> <tr> <td>NPT Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)</td> <td>NP</td> </tr> <tr> <td>BSP Female (2" C70, 2" K10)</td> <td>BA</td> </tr> <tr> <td>NPT Female (2" C70, 2" K10)</td> <td>NA</td> </tr> <tr> <td rowspan="5">Flanged</td> <td>ISO PN10</td> <td>10</td> </tr> <tr> <td>ISO PN16</td> <td>16</td> </tr> <tr> <td>ANSI 150</td> <td>A5</td> </tr> <tr> <td>ABNT 16</td> <td>B6</td> </tr> <tr> <td>AS16</td> <td>SA</td> </tr> <tr> <td rowspan="2">Flange Adaptors</td> <td>Universal Flange (ISO 10/16, AS16) connected to BSP male (C10/C30 2-3", C50 2-3-4")</td> <td>FF</td> </tr> <tr> <td>Universal Flange (ANSI 150) connected to NPT male (C10/C30 2"-3", C50 2"-4")</td> <td>FN</td> </tr> </tbody> </table>		End Connections / Pressure Ratings	Code	Threaded	BSP Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)	BP	NPT Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)	NP	BSP Female (2" C70, 2" K10)	BA	NPT Female (2" C70, 2" K10)	NA	Flanged	ISO PN10	10	ISO PN16	16	ANSI 150	A5	ABNT 16	B6	AS16	SA	Flange Adaptors	Universal Flange (ISO 10/16, AS16) connected to BSP male (C10/C30 2-3", C50 2-3-4")	FF	Universal Flange (ANSI 150) connected to NPT male (C10/C30 2"-3", C50 2"-4")	FN	<table border="1"> <thead> <tr> <th>Additional Attributes</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Stainless Steel Pressure Test Point (Schrader Valve)</td> <td>T</td> </tr> <tr> <td>Pressure Test Point</td> <td>5</td> </tr> <tr> <td>Lower Service Port 1/8" NPT (3/4"-1" A10/A30, C10/C30) or 1/4" NPT (2-3" C10/C30, C70, C75)</td> <td>P</td> </tr> <tr> <td>3/4" Female threaded Outlet (3/4"-1" A10/A30 C10/C30)</td> <td>t</td> </tr> <tr> <td>Insect Screen (C70, C75)</td> <td>S</td> </tr> <tr> <td>Drainage Valve (C10, C30, C50, C70, C75)</td> <td>Z</td> </tr> <tr> <td>Stainless Steel lower float (C50)</td> <td>N</td> </tr> </tbody> </table>		Additional Attributes	Code	Stainless Steel Pressure Test Point (Schrader Valve)	T	Pressure Test Point	5	Lower Service Port 1/8" NPT (3/4"-1" A10/A30, C10/C30) or 1/4" NPT (2-3" C10/C30, C70, C75)	P	3/4" Female threaded Outlet (3/4"-1" A10/A30 C10/C30)	t	Insect Screen (C70, C75)	S	Drainage Valve (C10, C30, C50, C70, C75)	Z	Stainless Steel lower float (C50)	N
Primary Feature (Model)	Code																																																																							
Vacuum Breaker 1/2"; DN12 PN10	ARV																																																																							
Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN10	A10																																																																							
Automatic (Air Release) Air Valve 3/4"-1"; DN20-25, PN16	A30																																																																							
Kinetic (Air-Vacuum) Air Valve 3/4"-2"; DN20-50, PN10	K10																																																																							
Combination Air Valve 3/4"-3"; DN20-80, PN10	C10																																																																							
Combination Air Valve 2"; DN50, PN10	C15																																																																							
Combination Air Valve 3/4"-3"; DN20-80, PN16	C30																																																																							
Combination Air Valve 2"; DN50, PN16	C35																																																																							
Combination Air Valve for Sewage & Wastewater 2"-4"; DN50-100, PN10 PN16	C50																																																																							
Combination Air Valve - Metal 2"-10"; DN50-250, PN16 PN25 PN40	C70																																																																							
Combination Air Valve - Metal 3"-12"; DN80-300, PN16 PN25 PN40	C75																																																																							
End Connections / Pressure Ratings	Code																																																																							
Threaded	BSP Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)	BP																																																																						
	NPT Male (A10/A30, 3/4"-1" K10, C10/C30, C15/C35, C50)	NP																																																																						
	BSP Female (2" C70, 2" K10)	BA																																																																						
	NPT Female (2" C70, 2" K10)	NA																																																																						
Flanged	ISO PN10	10																																																																						
	ISO PN16	16																																																																						
	ANSI 150	A5																																																																						
	ABNT 16	B6																																																																						
	AS16	SA																																																																						
Flange Adaptors	Universal Flange (ISO 10/16, AS16) connected to BSP male (C10/C30 2-3", C50 2-3-4")	FF																																																																						
	Universal Flange (ANSI 150) connected to NPT male (C10/C30 2"-3", C50 2"-4")	FN																																																																						
Additional Attributes	Code																																																																							
Stainless Steel Pressure Test Point (Schrader Valve)	T																																																																							
Pressure Test Point	5																																																																							
Lower Service Port 1/8" NPT (3/4"-1" A10/A30, C10/C30) or 1/4" NPT (2-3" C10/C30, C70, C75)	P																																																																							
3/4" Female threaded Outlet (3/4"-1" A10/A30 C10/C30)	t																																																																							
Insect Screen (C70, C75)	S																																																																							
Drainage Valve (C10, C30, C50, C70, C75)	Z																																																																							
Stainless Steel lower float (C50)	N																																																																							
<table border="1"> <thead> <tr> <th>Additional Features</th> <th>Code</th> </tr> </thead> <tbody> <tr> <td>Without Additional Feature</td> <td>00</td> </tr> <tr> <td>Surge Protection (Anti-slam) (C10/C30 - 2"-3", C50, C70, C75)</td> <td>SP</td> </tr> <tr> <td>Assisted Closing (C10/C30 - 2"-3", C50, C70, C75)</td> <td>AC</td> </tr> <tr> <td>Inflow Prevention (C10/C30 - 2"-3", C50, C70 - 2"-6" side outlet)</td> <td>IP</td> </tr> </tbody> </table>		Additional Features	Code	Without Additional Feature	00	Surge Protection (Anti-slam) (C10/C30 - 2"-3", C50, C70, C75)	SP	Assisted Closing (C10/C30 - 2"-3", C50, C70, C75)	AC	Inflow Prevention (C10/C30 - 2"-3", C50, C70 - 2"-6" side outlet)	IP																																																													
Additional Features	Code																																																																							
Without Additional Feature	00																																																																							
Surge Protection (Anti-slam) (C10/C30 - 2"-3", C50, C70, C75)	SP																																																																							
Assisted Closing (C10/C30 - 2"-3", C50, C70, C75)	AC																																																																							
Inflow Prevention (C10/C30 - 2"-3", C50, C70 - 2"-6" side outlet)	IP																																																																							