

LEVEL CONTROL & PRESSURE SUSTAINING VALVE

with Modulating Vertical Float

Model 753-67

Hydraulically operated, level control and pressure sustaining control valve that controls reservoir filling and reservoir level. During filling the valve sustains minimum upstream pressure regardless of fluctuating flow or reservoir level. Reservoir filling is in response to a hydraulically controlled modulating vertical float that maintains a constant water level, regardless of fluctuating demand (can be used on reservoir intake or outtake according to application).

The BERMAD 700 SIGMA EN/ES series valves are hydraulic globe valves with a raised seat and double chamber actuator. They provide unobstructed flow, effective high-pressure modulation, and minimal cavitation, complying with various potable water standards.




Features & Benefits




- Designed to - stand up to the toughest conditions
 - Excellent anti-cavitation properties
 - Wide flow range
 - High stability and accuracy
 - Drip tight sealing
- Double chamber design
 - Moderated valve reaction
 - Protected diaphragm
 - Optional operation in very low pressure
 - Moderated closing curve
- Flexible design - Easy addition of features
- Obstacle free flow pass
- V-Port Throttling Plug (Optional) - Very stable at low flow
- Compatible with various standards
- High quality materials
- In-line serviceable - Easy maintenance

Major Additional Features

- Closing & Opening speed control – 753-03-67
 - Closing surge prevention – 753-67-49
 - Electric float backup – 753-67-65
 - Independent Check Feature – 753-67-2S
- See relevant BERMAD publication*

Typical Installation





This drawing refers to 1½ – 8"; 40-200 mm sized valves only. For other sizes please refer to the Model's IOM.

Main Valve

Size Range:

EN Series: 1½"-16"; DN40-400

ES Series: 2½"-24"; DN65-600

Pattern: "Y" (globe)

Pressure Rating: 25 bar

End Connection: Flanged

Temperature Rating: 60°C

Plug Types: Flat disc, V-port, Cavitation cage

Optional higher temperature: Available on request

Standard Materials:

Body & Cover: Ductile Iron

Bolts, Nuts & Studs: Stainless Steel

Internals: Stainless Steel, Tin Bronze, Coated Steel & POM

Diaphragm: Fabric-reinforced synthetic rubber

Seals: Synthetic rubber

Coating: Dark blue Fusion bonded epoxy

For other materials contact BERMAD

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass

Tubing: Stainless Steel or Copper

Fittings: Stainless Steel or Brass

Pilot standard materials:

Body: Stainless Steel, Bronze & Brass

Elastomers: Synthetic Rubber

Internals and Spring: Stainless Steel

Pilot Options:

Various pilots and calibration springs are available.

Select according to valve size and operating conditions.

For more details check relevant pilots product pages.

Float standard materials:

Pilot Body: Brass

Elastomers: NBR

Internal Parts: Stainless Steel 316 & Brass

Lever System: Brass

Float: Plastic

Float Rod: Stainless Steel 316

Base Plate: Stainless Steel 316

Float optional materials:

Metal Parts: Stainless Steel 316

Elastomers: EPDM

Notes

- Each extension rod adds 560 mm; 22". One extension rod is supplied.
- Extra counterweight is required if second extension rod is used.
- If inlet pressure is below 0.5 bar / 7psi or above 10 bar /150 psi, consult factory.
- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing.
- Recommended maximum flow velocity: 6.0 m/sec; 20 ft/sec.
- See BERMAD float installation recommendation.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the BERMAD website.

