

STRAINER (STONE AND GRAVEL TRAP)

Model 80F

The BERMAD 80F Strainer is engineered to effectively remove foreign matter such as stones, sticks, and other debris from the pipeline.

It is recommended to install the strainer upstream of control valves, flow meters, and other system appliances to ensure optimal performance and protection.

Features

- Large trap capacity
- Low pressure loss
- Blow-off port for easy cleaning
- In-line serviceable
- Certified for potable water



Technical Data

Main Valve:

Valve Patterns: "Y" (Globe)

Size Range: 1½"-10"; DN40-250

Pressure Rating: 40 bar

End Connections: Flanged, Grooved

Temperature Rating: 60°C

Standard materials:

Body: Ductile Iron

Cover: Carbon Steel

Bolts & Nuts: Stainless Steel

Screen / Basket: Stainless Steel 304

Seals: Synthetic rubber

Coating: Dark blue Fusion bonded epoxy

Optional materials:

Body: Stainless Steel 316

Cover: Stainless Steel 316

Screen / Basket: Stainless Steel 316

Technical Specifications

Dimensions and Weights (80F-EN)

Size		L	H	W	B (Standard)	B (Optional)	Basket Hole Diameter
Inch	DN	mm	mm	Kg	Inch	Inch	mm
1½"	40	230	120	9.8			
2"	50	230	127	11.8	G ¾"	NPT ¾"	2
2½"	65	290	169	17.8		-	
3"	80	310	194	23			
4"	100	350	245	38	G 1½"		4
6"	150	480	270	69		NPT 1½"	
8"	200	600	365	107	G 2"		5
10"	250	730	450	164		-	

Flow Factor

Valve Size	Inch	1½"	2"	2½"	3"	4"	6"	8"	10"
	DN	40	50	65	80	100	150	200	250
Kv		57	62	45	98	130	200	540	1480

