

ELECTRONIC CONTROL VALVE

with Opening and Closing Speed Controls

Model 718-03-M5-M5M-M5L

Electronic control valve that combines the advantages of an excellent modulating, line pressure driven, hydraulic control valve with those of electronic control. In response to signals from the electronic controller, the valve changes its opening position per preset values programmed into the controller. Both the valve's opening and closing speeds are controllable and on-site adjustable.

The BERMAD 700 Series large control valves are hydraulically operated and diaphragm actuated. Their unique hydro-dynamic globe design with an open plug ensures high flow capabilities.




Features & Benefits



- Hydrodynamic wide globe valve body provides:
 - Higher flow coefficient (Kv; Cv) than standard globe valves
 - Higher resistance to cavitation damage
- In-line serviceable
- Valves are suitable for working with all types of command: Hydraulic, Electric and Pneumatic.
- Self-operated valves that can work without an external source of power
- Wide range of options and accessories:
 - Visual position indicator
 - Limit switches
 - Analog opening output
 - Large selection of control accessories
 - Large inspection and service ports (700-M5L)

Typical Applications


- Industrial and municipal systems - Pressure and flow regulation
- Mixing junctions control
- Water treatment plants - Process control

Typical Installation





Closed



Open

Main Valve

Size Range: 20"-36"; DN500-900

Pattern: Globe

Pressure Rating: 25 bar

End Connection: Flanged

Temperature Rating: 80°C

For 60-80°C consult factory

Standard Materials:

Body & Cover: Ductile Iron

Cover Bolts: Stainless Steel

Internals: Epoxy coated Ductile Iron, Stainless Steel & Tin Bronze

Diaphragm: Fabric-reinforced synthetic rubber

Seals: Synthetic rubber

Coating: Dark blue Fusion bonded epoxy

For other materials contact BERMAD

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass

Tubing: Stainless Steel or Copper

Fittings: Stainless Steel or Brass

Solenoid standard materials:

Body: Brass or Stainless Steel

Elastomers: NBR or FPM

Enclosure: Molded Epoxy

Solenoid Electrical Data:

Voltages:

(AC): 24, 110-120, 220-240, (50-60Hz)

(DC): 12, 24, 110, 220

Power Consumption:

(AC): 30VA, inrush; 15VA (8W), holding or 70VA, inrush; 40VA (17.1W), holding

(DC): 8-11.6W

Values may vary according to specific solenoid model.

For more details check solenoid product page.

Notes

- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing and cavitation analysis.
- Recommended maximum flow velocity: 6.0 m/sec; 20 ft/sec.
- Minimum operating pressure: 0.7 bar; 10 psi. For lower pressure requirements consult factory.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the [BERMAD](https://www.bermad.com) website.



www.bermad.com

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.

© Copyright 2015-2025 BERMAD CS Ltd

October 2025