


LEVEL CONTROL VALVE

with Modulating Vertical Float

Model 750-67-M5-M5M-M5L

Hydraulically operated control valve that controls reservoir filling and reservoir level. Reservoir filling is in response to a hydraulically controlled modulating vertical float that maintains a constant water level, regardless of fluctuating demand (can be used on reservoir intake or outtake according to application).

The BERMAD 700 Series large control valves are hydraulically operated and diaphragm actuated. Their unique hydro-dynamic globe design with an open plug ensures high flow capabilities.




Features & Benefits



- Hydrodynamic wide globe valve body provides:
 - Higher flow coefficient (Kv; Cv) than standard globe valves
 - Higher resistance to cavitation damage
- In-line serviceable
- Valves are suitable for working with all types of command: Hydraulic, Electric and Pneumatic.
- Self-operated valves that can work without an external source of power
- Wide range of options and accessories:
 - Visual position indicator
 - Limit switches
 - Analog opening output
 - Large selection of control accessories
 - Large inspection and service ports (700-M5L)

Typical Applications


- Level control for water reservoirs
- "Always full" - Maximizing the use of reservoir volume

Typical Installation





Closed



Regulating

Main Valve

Size Range: 20"-36"; DN500-900

Pattern: Globe

Pressure Rating: 25 bar

End Connection: Flanged

Temperature Rating: 80°C

For 60–80°C consult factory

Standard Materials:

Body & Cover: Ductile Iron

Cover Bolts: Stainless Steel

Internals: Epoxy coated Ductile Iron, Stainless Steel & Tin Bronze

Diaphragm: Fabric-reinforced synthetic rubber

Seals: Synthetic rubber

Coating: Dark blue Fusion bonded epoxy

For other materials contact BERMAD

Control System

Standard Materials:

Accessories: Stainless Steel, Bronze & Brass

Tubing: Stainless Steel or Copper

Fittings: Stainless Steel or Brass

Float standard materials:

Pilot Body: Brass

Elastomers: NBR

Internal Parts: Stainless Steel 316 & Brass

Lever System: Brass

Float: Plastic

Float Rod: Stainless Steel 316

Base Plate: Stainless Steel 316

Float optional materials:

Metal Parts: Stainless Steel 316

Elastomers: EPDM

Notes

- Minimum level differential: 150mm; 6'34";.
- Maximum level differential: 540mm; 2'1'34";.
- Each extension rod adds 560 mm; 22". One extension rod is supplied.
- Extra counterweight is required if second extension rod is used.
- If inlet pressure is below 0.5 bar / 7psi or above 10 bar / 150 psi, consult factory.
- Inlet Pressure, Outlet Pressure and Flow-rate are required for optimal sizing.
- Recommended maximum flow velocity: 6.0 m/sec; 20 ft/sec.
- Minimum operating pressure: 0.7 bar; 10 psi. For lower pressure requirements consult factory.
- See BERMAD float installation recommendation.

For detailed Engineering & Specification data, IOM and CAD Drawings, visit the Model Page on the [BERMAD](https://www.bermad.com) website.



www.bermad.com

The information contained herein may be changed by BERMAD without notice. BERMAD shall not be held liable for any errors.

© Copyright 2015-2025 BERMAD CS Ltd

October 2025